



ELEVATION

NOTES:

1. SPECIFICATIONS AND LENGTH OF PIPE FOR CROSSINGS SHALL BE AS SHOWN ON THE SPECIFIC PROFILE DRAWINGS. NO VERTICAL BENDS SHALL BE MADE WITHIN THESE LIMITS.
2. INSTALLATION SHALL BE MADE IN ACCORDANCE WITH APPLICABLE PERMIT.
3. THE TRENCH EXCAVATED FOR THE PIPELINE SHALL BE PROMPTLY BACKFILLED IN A PROPER AND WORKMANLIKE MANNER SO AS TO LEAVE NO VOIDS OR OBSTRUCTIONS THEREIN AND SO AS TO FURNISH AND PROVIDE DRAINAGE.
4. ROAD CROSSING PIPE SHALL EXTEND TO A MINIMUM OF 3' BEYOND TOE OF SLOPE (TYPICAL EACH SIDE). FULL JOINTS OF PIPE SHALL BE USED UNLESS DIRECTED OTHERWISE BY ENGINEER.
5. INSTALL CATHODIC PROTECTION TEST STATION PER STANDARD DRAWING WHERE DESIGNATED BY COMPANY. SEE DRAWING STD-ENC-X-RDSC FOR PIPE CROSSINGS WITH LESS THAN 5'-6" COVER.



STANDARD ENCROACHMENT DETAILS FOR ROAD CROSSING

REV.	DATE	BY	DESCRIPTION	APP	SCALE: 1" = 1'-0"
0	05-05-2004	GLS	REVISED PER SSCGP STANDARDS	RDH	P. I. N.
1	11-05-2007	JAK	REPLACED STD. DWG. 005-002-A-0062	RDH	DWG. NO.
					STD-ENC-X-RD

DRAWN BY: GLS DATE: 05-05-2004
 CHECKED BY: DATE:
 APPROVED BY: RDH DATE: 05-28-2004